

Field Accuracy Test of RPAS Photogrammetry

P. Barry, R. Coakley

Baseline Surveys Ltd

Mount Desert Lodge, Lee Road, Cork, Co. Cork - Ireland
paudie@baselinesurveys.ie

KEY WORDS: RPAS, Accuracy of RPAS Photogrammetry, UAS Photogrammetry, Orthomosaic, DEM, Topographic Surveying.

ABSTRACT:

Baseline Surveys Ltd is a company which specialises in the supply of accurate geospatial data, such as cadastral, topographic and engineering survey data to commercial and government bodies. Baseline Surveys Ltd invested in aerial drone photogrammetric technology and needed to establish the accuracy of the geographic data derived from our RPAS photogrammetry before marketing our new aerial mapping service. Having supplied the construction industry with survey data for more than 20 years, we felt that it was crucial for our clients to clearly understand the accuracy of our photogrammetry so they can safely make informed spatial decisions, within the known accuracy limitations of our data. This information would also inform us on how and where RPAS photogrammetry can be utilised.

The specific information we required was the actual accuracy that can be reliably achieved using a RPAS to collect data under field conditions throughout a typical 2Ha site. We flew a RPAS over the test area in a typical matrix pattern with an 80% front and 80% side overlap; we placed 45 ground markers as check points and surveyed them in using network RTK GPS. We specifically designed the ground markers to meet our accuracy needs. We established 10 separate control points and inputted these into our photo modelling software. The rest of the GPS coordinated check marker data were added later in ArcMap to the completed orthomosaic and digital elevation model so we could accurately compare the RPAS photogrammetry XYZ data with the RTK GPS XYZ data at highly reliable common points. The accuracy we achieved throughout the 45 check points was 95% reliably within 41mm horizontally and 68mm vertically and with a 1cm ground sample distance. This finding has shown that XYZ data derived from RPAS photogrammetry has a similar practical accuracy to RTK GPS, which is commonly used for cadastral, topographic and engineering survey work. This means that RPAS photogrammetry can replace GPS surveying as the main method of data capture for engineering projects, boundary mapping and topographical surveying. Aerial Photogrammetry can now be used for projects with a 1:200 map scale accuracy requirement.

1. INTRODUCTION

Much of current land, engineering and cadastral survey work using GPS and total station is often labour intensive, sometimes involves surveyors working in hazardous environments and the completeness of the data captured often depends on the time allotted to the survey project. No representation of geography is perfect and certainly the point, text, line and polygon style of 21st century digital mapping is no exception. GPS and Total station geographic data collection methods are accurate enough to design civil engineering and architectural projects with sufficient practical accuracy (within +/-5cm) to design roads, bridges, pipelines, buildings etc. Although GPS data is highly spatially accurate in both absolute and relative terms it completely falls down in richness of data. Each line, point and polygon must be described by textual means in order to communicate its geographic meaning. Its completeness is something we don't dare even to consider doubting, but there is an undeniable risk of a surveyor omitting data without even realising. This style of data collection is often time consuming and by nature expensive. As Surveyors, we wanted to experiment with RPAS photogrammetry to see if it would be accurate enough to replace current GPS and total station survey methods in Engineering, Cadastral and Topographic Surveys.

This would revolutionise the world of Engineering Surveying in terms of vastly reducing data capture cost while vastly increasing data quality and richness.

As we were practically pushing beyond the current accuracy limitation of RPAS derived geographic data, we decided to use the C-Astral Bramor RPAS for its superior stability as an aerial data capture platform. Its stability being achieved by a combination of its aerodynamics and high end Lockheed Martin designed Autopilot system. The high 24MP precision of its Sony Nex-7 camera was another deciding factor along with its very clever safety feature of a remotely deployable parachute landing option. It also has 3hr endurance and a practical wind tolerance of 20knots when piloted by an experienced RPAS crew.

While we had decided on using Network RTK GPS to establish Irish Transverse Mercator coordinates on the centre positions of the ground control points, we carefully designed geometrically patterned ground markers which allowed us to obtain sub pixel accuracy of the centre point location when identifying ground marker positions at the post data collection and pre-processing stage.

Agisoft Photoscan was the software we decided to use for its stated accuracy 1-3 pixels and the high quality of the ortho photography and digital elevation model outputs.

ArcMap was used for presenting the final fusion of data captured by RPAS and GPS.

2. PRE-FLIGHT PLANNING

The 9 ground control markers were theoretically positioned so that they were equidistantly distributed throughout the site to ensure an even distribution of errors.




Figure 1: Ground control station and check point targets

A flight plan was generated so that that an 80% overlap and a 80 % sidelap and at an altitude of 90m to provide an expected GSD of 10mm. Flight direction was plotted at 90 degrees to the actual wind direction so as to maintain a constant ground speed of less than 16m/s during the photographic process. This step helped to reduce ground smear, a phenomenon which blurs the pixels due to the movement of the RPAS.

3. DATA ACQUISITION SYSTEM

The data acquisition system we used on this project is a hybrid of Trimble GoeXR Network RTK GPS and a C-Astral Bramor RPAS. We used the RTK GPS to establish ITM coordinates on our specifically designed ground markers to provide photo control. The GPS unit has a spatial accuracy in the region of 10-25mm both horizontally and vertically, due to the fact that we used struts to maintain steadiness during NRTK readings.



Figure 2: The stabilised Trimble GoeXR Network RTK GPS used to get the coordinates of the target centres.

The C-Astral Bramor RPAS platform is a blended wing constructed of Kevlar and carbon fibre and has a 4kg

MTOM. It is catapult launched, has extremely steady flight characteristics and advanced safety features afforded by its Lockheed Martin autopilot including a parachute deployment system for emergency and routine landing procedures. It carries a Sony Nex-7 24MP RGB sensor, which is oriented in portrait which allows for more forward overlap at a slower triggering interval. Our ground control markers were carefully designed so the most exact centre of the marker could be determined with a very high degree of accuracy from the photography at the processing stage.



Figure 3: The C-Astral Bramor RPAS on the catapult ready for launch.

4. ON SITE CONDITIONS

As Surveyors we wanted to carry out our accuracy test in every day conditions which, by their very nature, are sub optimal. The prevailing weather conditions on the day of our flight test were cloudy with intermittent sunny spells with a wind speed at our flying altitude of 90m AGL was a maximum of 7m/s. The wind direction at altitude diverged from that used in our pre flight planning by 20 degrees. This had the effect on the RPAS of getting a 10m/s variation in its ground speed when travelling with and against the wind.



Figure 4: The C-Astral Bramor RPAS during the initial deployment of its landing parachute.

The topography of the site had a 5m variation in level, was surrounded by mature woodland up to 25m in height and had numerous buildings which would all contribute to turbulence at our flying altitude.

5. DATA PROCESSING

Firstly 10 control stations and 45 check points, which were surveyed by Network RTK GPS in Irenet95 coordinates, were downloaded into Geosite office 5.1 and exported to AutoCADIt 2013 as two separate files.




Figure 5: The targets as seen in the Orthomosaic. Note the black dot which represents where the centre of the target should be according to the Trimble GoeXR Network RTK GPS.

We downloaded 1601 photographs from the Bramor RPAS along with the log file, which contains photo GPS position, barometric height, roll, pitch and yaw. We imported the photos and the logfile into Agisoft photoscan and using the software we eliminated superfluous photographs by deleting photos with high roll values, which occurred at turns. The refined 728 photographs were then used for the photo alignment stage; the reason why we used an oversized area is that we felt that the additional photographs would contribute to alignment accuracy of the target area. We then imported the 10 control stations into photoscan and identified the centre of each control point marker on each photo and attached it with its appropriate coordinate value.

Of the 728 photographs we then used 168 photographs to further process the data into a 3D model for subsequent orthophoto and DEM output. The orthophoto was outputted at a resolution of 10.2mm pixel size and the DEM was outputted at 20mm GSD.



Figure 6: The detail of 1cm orthophotography can be seen here. This is a view looking down through the

atrium over the dinning area of the surveyed hotel. Note the cutlery on the table.

The resulting ITM geo referenced orthophoto and DEM were imported into ArcGIS along with the GPS CAD data. Distances were measured from the centre of the target, as they appeared on the orthophoto, to the centre of the target as measured by GPS by using the ArcGIS measure tool to attain the distance between both readings. GPS level point data were compared with DEM readings at the same point. Results were then recorded as shown in figure 6.

6. RESULTS

The resulting geo-referenced orthophoto and DEM Where imported into ArcMap along with the coordinated data from the RTK GPS. The difference between the two data sets is shown in Figure 7 below.

Point No.	XY Error m	Z Error m	Point No.	XY Error m	Z Error m
1	0.025	0.06	24	0.008	0.02
2	0.023	0.02	25	0.000	0.03
3	0.014	0.01	26	0.004	-0.02
4	0.014	-0.04	27	0.012	0.03
5	0.018	-0.05	28	0.011	0.00
6	0.020	-0.02	29	0.029	0.02
7	0.035	-0.02	30	0.023	-0.05
8	0.019	-0.01	31	0.021	-0.04
9	0.010	0.04	32	0.010	-0.02
10	0.043	0.01	33	0.031	-0.07
11	0.041	0.04	34	0.007	-0.01
12	0.015	-0.01	35	0.026	-0.02
13	0.040	-0.01	36	0.040	-0.07
14	0.016	-0.02	37	0.007	-0.04
15	0.016	-0.02	38	0.012	-0.03
16	0.017	-0.03	39	0.007	-0.03
17	0.006	-0.02	40	0.025	0.02
18	0.047	-0.04	41	0.012	0.03
19	0.023	-0.02	42	0.033	0.03
20	0.008	0.05	43	0.024	0.07
21	0.010	0.00	44	0.015	0.01
22	0.013	-0.01	45	0.011	0.03
23	0.016	0.00			

Figure 7: The dataset of measured errors between the Orthomosaic/DEM Network RTK GPS for the target centers.

Label	X error (m)	Y error (m)	Z error (m)	Error (m)	Projections	Error (pix)
point 1	0.001958	0.001193	-0.000491	0.002344	33	1.277433
point 10	0.009328	-0.026748	-0.012029	0.030776	9	0.883605
point 2	0.000012	-0.003082	-0.024623	0.024815	35	1.419103
point 3	-0.004135	0.010068	0.006149	0.012501	21	1.063595
point 4	0.007812	0.009205	0.012708	0.017529	20	1.610777
point 5	-0.000001	0.003609	0.007510	0.008332	18	0.551958
point 6	-0.004106	-0.003277	0.012169	0.013255	19	0.574836
point 7	-0.000441	-0.002176	-0.010497	0.010729	20	0.752000
point 8	-0.002598	-0.004642	-0.006060	0.008064	16	0.845599
point 9	-0.006739	0.000893	-0.016638	0.017973	18	0.610214

Figure 8: Control Point Errors

The above results were imputed to Microstation to produce the graphs shown in figures 9 and 10.




Figure 9: The planimetric distribution of errors derived from the figures in the table shown in figure 7.




Figure 10: The distribution of vertical of errors derived from the figures in the table shown in figure 7.

From the table shown in figure 7, the following results were obtained.

	XY m	Z m
Mean	0.021	0.031
RSME	0.023	0.035
Accuracy 95%	0.041	0.068

Figure 11: The Mean, RSME and the Accuracy derived from the figures in the table shown in figure 7. Accuracy at 95% confidence level is taken as planimetrically 1.7308 x RMSEr and vertically as 1.9600 x RMSEz. Source - Geospatial Positioning Accuracy Standards. Part 3: National Standard for Spatial Data Accuracy.

7. DISCUSSION

The significance of the ability of a RPAS to capture geographic data at similar accuracies to RTK GPS along with the richness of detail which can only be revealed by 10mm GSD aerial photography is truly revolutionary. Like all disruptive technologies, RPAS photogrammetry will take a couple of years to become main stream, but when it does it will almost fully replace current methods of Engineering Surveying. The accuracy that can be achieved by RPAS photogrammetry is within 1:200 scales according to NSDI & FGDC mapping accuracy standards during sub-optimal conditions

Now that RPAS can be used to map at scales up to 1:200, RPASs will start to take over from GPS and total station as the main survey grade data collection method as RPASs are far more efficient at capturing geographic data, offering a huge financial advantage to government agencies and private companies using RPAS technology to collect geographic data, particularly over more detailed and larger sites.

Apart from an enormous time saving on data collection without an appreciable loss in accuracy, RPAS aerial photogrammetry offers far richer data than conventional survey vector data consisting of points, text and lines. Instead RPAS photogrammetry offers the user a bird's eye view of the site without any need for text or any fear of data being omitted. The accuracy to which levels are generated by the photogrammetry allows for contouring at 0.2m intervals which is very encouraging, GPS readings would still be required for manhole covers, Finished Floor levels etc., but even so, this still represents a huge leap forward in terms of surveying efficiency.

In terms of representing the landscape, the orthophoto can be combined with the DEM to produce very accurate photorealistic 3D modelling in programmes such as ArcScene and can be analysed to yield highly accurate earthmoving volumetric calculations.

This is the most spatially accurate aerial survey data that we could currently find anywhere on the internet.




Figure 12: The outputted Orthomosaic.

8. REFERENCES

References from websites:

- Eisenbeiss H., 2004. RPAS Photogrammetry. [online] Available at: http://www.igp-data.ethz.ch/berichte/blaue_Berichte_PDF/105.pdf . [Accessed 03 April 2013]
- Niranjan et al., 2007. Initial Efforts toward Mission-Specific Imaging Surveys from Aerial Exploring Platforms: RPAS. [online] Available at: http://www.gisdevelopment.net/proceedings/mapworldforum/poster/MWF_Poster_127.pdf. [Accessed 06 April 2013]
- Bendea et al., 2007. Mapping of Archeological Areas using a Low Cost RPAS. [online] Available at: <http://www.isprs.org/proceedings/XXXVI/5-C53/papers/FP025.pdf>. [Accessed 06 April 2013]
- Puschel H., 2009. Set up of a Photogrammetric test field for RPAS-Platforms. [online] Available at: http://www.igp.ethz.ch/photogrammetry/.../RPAS_Testfield_klein.pdf. [Accessed 07 April 2013]
- Vallet et al., 2011. Photogrammetric Performance of an Ultra Light Weight Swinglet "RPAS". [online] Available at: <http://www.isprs.org/proceedings/XXXVIII/1-C22/papers/vallet.pdf>. [Accessed 7 April 2013]

Rock et al., 2011. Sensitivity Analysis of RPAS_Photogrammetry for Creating Digital Elevation Models (DEM). [online]Available at: http://www.geometh.ethz.ch/auv_g/rock_presentation. [Accessed 08 April 2013]

Haala et al., 2011. Performance Test on RPAS-BasedPhotogrammetric Data Collection. [online]Available at: <http://www.isprs.org/proceedings/XXXVIII/1-C22/papers/haala.pdf>. [Accessed 9 April 2013]

Kung et a., 2011. The Accuracy of Automatic Photogrammetric Techniques on Ultra-Light RPAS Imagery. [online]Available at: <http://www.isprs.org/proceedings/XXXVIII/1-C22/papers/strecha.pdf>. [Accessed 9 April 2013]

The American Society for Photogrammetry and Remote Sensing, 1990.
ASPRS ACCURACY STANDARDS FOR LARGE-SCALE MAPS.

Subcommittee for Base Cartographic Data Federal Geographic Data Committee, 1996.
Geospatial Positioning Accuracy Standards.
Part 3: National Standard for Spatial Data Accuracy.